

TRÓJNIKI
EN 10253-2

Trójniki redukcyjne - Wymiary c.d.

Końcówka D		Końcówka D ₁		F	G
DN	D	DN ₁	D ₁		
350	355,6	150	168,3	279	238
		200	219,1		248
		250	273		257
		300	323,9		270
400	406,4	150	168,3	305	264
		200	219,1		273
		250	273		283
		300	323,9		295
450	457	200	219,1	343	298
		250	273		308
		300	323,9		321
		350	355,6		330
500	508	400	406,4	381	330
		250	273		333
		300	323,9		346
		400	406,4		356
550	559	450	457,0	419	368
		250	273		359
		300	323,9		371
		400	406,4		381
600	610	500	508,0	432	406
		250	273		384
		300	323,9		397
		400	406,4		406
650	660	500	508,0	495	432
		300	323,9		422
		350	355,6		432
		400	406,4		432
700	711	500	508	521	457
		300	323,9		448
		400	406,4		457
		500	508,0		483
750	762	600	610,0	559	508
		400	406,4		483
		500	508,0		508
		600	610,0		533
800	813	400	406,4	602	508
		500	508,0		533
		600	610,0		559
		700	711,0		572
850	864	400	406,4	635	533
		500	508,0		559
		600	610,0		584
		700	711,0		597