

DNO KOSZYKOWE
EN 10253-2

Wymiary c.d.										
Średnica		Szeregi grubości ścianki								
DN	D	D	1	2	3	4	5	6	7	8
250	273		5	6,3	8,8	10,0	12,5	16,0	22,2	30,0
300	323,9		5,6	7,1	8,8	10,0	12,5	17,5	25,0	32,0
350	355,6		5,6	8,0	10,0	12,5	16,0	20,0	28,0	36,0
400	406,4		6,3	8,8	10,0	12,5	17,5	22,2	30,0	40,0
450	457		6,3	10,0	11,0	12,5	17,5	22,2	32,0	45,0
500	508		6,3	10,0	11,0	12,5	17,5	25,0	36,0	50,0
550		559	6,3	10,0		12,5	20,0	28,0		
600	610		6,3	10,0	12,5	17,5	25,0	30,0	45,0	60,0
650	660			10,0	12,5	17,5				
700	711		7,1	10,0	12,5	25,0				
750		762		10,0	12,5	25,0				
800	813		8,0	10,0	12,5	25,0				
850		864		10,0	12,5	25,0				
900	914		10,0	12,5	20,0	25,0				
1 000	1 016		10,0	12,5	20,0	25,0				
1 050		1 067	10,0	12,5	20,0	25,0				
1 100		1 118	10,0	12,5	20,0	25,0				
1 150		1 168	10,0	12,5	20,0	25,0				
1 200	1 219		10,0	12,5	20,0	25,0				